

Lady Design Glaze

Surface: Plaster/CMU/Concrete/Gypsum Board Partition

Primer Coat

One coat: Jotun Fenomastic Emulsion Primer:

Vol. solids: 25±2 %

Filler Coat

Two coats: Jotun Stucco:

Vol. solids: 50% ±2 %

Topcoats

Two coats: Jotun Fenomastic My Home Smooth Silk

Vol. solids: 44±2 %

Properties

- **VOC content**
10.8 g/l (US EPA 24)
- **Washability/Scrub Resistance**
>10,000 scrubs (DIN 53778)
- **Hazardous Materials**
Free from:
 - Heavy Metals (ICP-AES)
 - APEO (BS 3762:90)
 - Formaldehyde (UV Spectroscopy)
 - Pthalates (GCMS)
- **Burnish Resistance**
Gloss Change:
60° =1.2 units
85° =3 units
- **Polish Resistance**
Gloss Change:
60° =1.8 units
85° =12.7 units
- **Contrast Ratio/whiteness**
94.00/94.88 (ASTM D2805-88)
- **Practical Washability**
Rating 0-2: (ASTM D4828:94)
- **Colour rub off**
Class A

(0 = All stains removed & 2 = No stains removed)

(Class A = Best & Class E = Worst]

Top coats:

Two coats Lady Design Glaze

Vol. solids: 43±2 %,